

Pendant Cable, Strain Relief, and Quick Disconnect

Pendant Cable



Conductix-Wampfler Pendant Cable has a yellow jacket and is resistant to sunlight, oil, and water.

Temperature Rating:

- Without External Strain Relief: -10°C to 90°C (14°F to 194°F)
- With External Strain Relief: -10°C to 105°C (14°F to 221°F)



UL & CSA approved

Standard Pendant Cable Without Strain Relief

Size AWG	No. of Conductors	Part No.	Diameter Nominal	Wt lb/ft (kg/m)
16	8	83092	0.465" (11.81)	0.145 (0.02005)
16	12	83093	0.550" (13.97)	0.200 (0.02765)
16	16	83094	0.605 (15.37)	0.255 (0.03526)
16	24	83095	0.745" (18.92)	0.375 (0.05185)
16	30	83096	0.785 (19.94)	0.455 (0.06291)
16	36	83097	0.885 (22.48)	0.540 (0.07466)



Authorized Sales & Service
J. HERBERT CORPORATION
 Call 1-800-255-0588
 407-846-0588 Fax: 846-1066
 info@jherbertcorp.com

Visit us online:
www.jherbertcorp.com

Standard Pendant Cable with Attached Strain Relief

Size AWG	No. of Conductors	Part No.	Diameter Nominal	Wt lb/ft (kg/m)
16	8	35398	0.515" (13.08)	.210
16	12	35399	0.575" (14.61)	.260
16	16	35400	0.630" (16.00)	.330
16	24	35401	0.760" (19.30)	.430



Note: The steel Strain Relief Cable(s), if externally attached or separate, is 1/8" diameter or 3/16" diameter with nylon jacket.

Round Pendant Cable with Internal Strain Relief

Size AWG	No. of Conductors	Part No.	Diameter Nominal	Wt lb/ft (kg/m)
16	3	34155	0.54" (13.72)	0.115
16	5	34155C	0.54" (13.72)	0.115
16	7	34635	0.62" (15.75)	0.230

Separate Strain Relief Cable and Hardware


Item	Description	Part No.
Separate Strain Relief Cable	3/16" Dia. Nylon Steel Cable (1/8" dia. w/o nylon) - 480 lbs. (217.72 kg) cap. Ordered in feet.	83098
Hardware Kit	Includes (2) Thimbles, (4) U-Clamps, and (1) Eye Bolt	83099
Hardware Kit	Used with cable 35398 thru 35401	36711
Hardware Kit	used with Quick Disconnect Trolley	39613

Quick Disconnect Plugs


Changing out a pendant has never been easier with these Quick Disconnect plug sets. Many other styles of connectors are available; please contact the factory.



Female Mount Base



Male End



Description	Part No.	"A" Dim	"B" Dim
Bulkhead Mount Base 16 Pin Female Insert	37766	4.06 (106)	3.39 (86)
Bulkhead Mount Base 24 Pin Female Insert	37767	4.41 (112)	5.12 (130)

Description	Part No.	"A" Dim	"B" Dim	"D" O.D.
Top Entry Hood 16 Pin Male Insert	41030	3.68 (93.5)	2.28 (57.9)	0.39-0.75 (9.9-19.0)
Top Entry Hood 24 Pin Male Insert	41032	4.72 (119.9)	3.58 (90.9)	0.70-1.06 (17.8-26.9)