Series Range

Authorized Sales & Service

J. HERBERT CORPORATION
Call 1-800-255-0588
407-846-0588 Fax: 846-1066
info@jherbertcorp.com

Visit us online:
www.jherbertcorp.com

Typical applications

- Stackers / reclaimers
- Bucket wheel excavators
- Tripper cars
- Mobile conveyors
- Scrapers
- Stack rakes



Extra long travel distance

Single or multi-layer drum type spool.

Skeleton-type drum

for optimal cable cooling and reduced inertia.

Modular platform construction

allows multiple arrangements and best fit with machine structure.

Rugged construction

for harsh environments.

Specifications

| Travel speed | Up to 60 m/min |
|---|--|
| Winding length | 2000 m max |
| OD of drum | Up to 3.3 m |
| Gearbox | BNA: 1000 N m – 18000 N m |
| | SMART Drive: 1000 N m - 8500 N m |
| Slip ring assembly (Also available with rotary joint for hose installation) | Power low voltage max: 690 V – 1600 A |
| | Power high voltage max: 36000 V – 500 A |
| | Control max: 500 V – 25 A |
| | Data: Ethernet 100 Mbps - 1 Gbps I Fiber optic Multimode - Single Mode |
| Temperature range | -40 °C – +60 °C |







